## AUTOMATED DATA COLLECTION
## AND TRANSMISSION

5

## PRIORITY AND RELATED APPLICATIONS

10

The present application claims priority to provisional patent application entitled, "Automated Order Entry Using Hand Held Device," filed on January 18, 2001 and assigned U.S. Application Serial No. 60/262,601.

## FIELD OF THE INVENTION

15

The present invention relates to data collection systems and more particularly relates to facilitating data collection and transmission through the use of a hand-held data entry computer.

## BACKGROUND OF THE INVENTION

Conventional data entry applications suffer from a well-known

20 accountability gap. In one form or another every automated system depends on the data with which it is provided. When humans are responsible for the provision of data to an automated system, human error can be propagated through the automated system and can result in unexpected errors and unintended consequences. Human errors include the entry of incorrect data and the failure to input expected data. The

25 accountability gap arises because the origin of the error is typically untraceable. Errors incur costs, but the final user of the data always bears these costs if no accountability exists.

The restaurant industry provides a good example of how erroneous data can wreak havoc in an automated system. In the foodservice industry, there are

30 primarily of two players: the restaurant and the distributor. The restaurant sells prepared food to its customers and buys food supplies from the distributor. The typical restaurant operates under tight constraints: it has a fixed menu and a predictable number of anticipated customers expecting to order prepared food from that menu. In addition, because food supplies are perishable, the restaurant has a

5    continually short lead-time.  As a result, the restaurant continually needs the food
supplies and needs them soon.  If, due to ordering errors, the distributor fails to
deliver the food supplies within the short lead-time, the restaurant will turn elsewhere
for its food supplies.  Thus the distributor is forced to take expensive measures to
correct the error within an extremely short time.  If the distributor delivers the wrong

10   food supplies, there is often not enough time to correct the delivery, and spoilage of
the wrong food supplies may result in its loss to the distributor.  In short, the
restaurant and the distributor both share the goal of delivering an accurate order of
food supplies within an agreed upon lead-time.

Unfortunately, the conventional order-entry systems used in the

15   restaurant industry often frustrate this shared goal.  Restaurants generally use two
kinds of orders: a standard order, which consists of largely the same items on a fairly
regular basis (e.g., weekly), and an on-demand order, which consists of items needed
on an unexpected basis (e.g., when supplies are depleted because a particular menu
item sells better than expected).  The standard order can be built and refined over time

20   and can, therefore, be quite stable.  The on-demand order is by definition, unstable
and unpredictable.  Restaurant personnel usually adjust a standard order prior to
placing it with the distributor.  For example, a restaurant employee will typically walk
through a stock room, a refrigerated room, and/or a freezer to determine which of the
standard order items have been depleted and what quantities of each should be

25   ordered.   Once the standard order has been adjusted to reflect these actual
requirements, the order can be placed

Typically, a designated restaurant employee contacts the distributor's
order entry personnel by telephone.  Reading from a handwritten standard order or
from a handwritten on-demand order, the restaurant employee verbally conveys the

30   order to the distributor's order entry employee.  The distributor's employee generally
records the order by hand on an order entry form.  Subsequently, the order entry form
may be passed to a data entry clerk who will enter the order into the automated order
entry system (i.e., computer).

Accordingly, there are multiple opportunities for error to enter and

35   propagate through the conventional order-entry system.  The order may be recorded
incorrectly or written illegibly by the restaurant personnel.  Even if the order is

2

5    accurately and legibly written, the restaurant personnel may read the order sheet incorrectly. The distributor's employee may record the order incorrectly on the order entry form. The order entry clerk may input the wrong data into the automated system. The probability of an error-causing event is increased by the fact that the personnel are typically not skilled in the restaurant business and lack the judgment to

10   question and correct errors as they occur.

Preprinted paper forms have been employed to reduce the errors described. While the use of forms tends to reduce errors, the written and verbal errors described are still an obstacle to accurate order entry.

An approach that has been attempted to reduce order entry error is the

15   use of on-line order entry systems. Such systems have the advantage of eliminating any misunderstanding between the restaurant and distributor personnel that may cause an error. These systems also reduce the error caused by any misunderstanding between personnel within the distributor. However, this approach requires the restaurant personnel to generate written orders prior to accessing the on-line order-

20   entry system. Accordingly, any errors generated by the initial step of recording the order by hand are not reduced or eliminated by such on-line order entry systems. In addition, on-line systems typically employ the Internet for data transmission, which remains a relatively unreliable data transmission means, particularly in an industry where timeliness is paramount.

25   While the problem of data entry errors has been described in relation to the restaurant industry, the reduction of human error during data entry into computing systems is a goal that is shared by any industry or endeavor that relies on data entry and the reliability of the entered data. In view of the foregoing, there is a need for a method of entering data and/or orders in an automated way that will reduce human

30   error in the order entry process. There exists a further need to reduce the opportunity for human data entry error in an automated data entry system. The method should further reduce the number of personnel needed to perform data entry in a single-enterprise or multiple-enterprise data entry environment.

## SUMMARY OF THE INVENTION

The present invention provides a system and method for automated data entry using an independent hand-held computer. The present invention can be implemented as a gateway between a data entry enterprise and a data collection enterprise. For example, the data entry enterprise may be a restaurant, while the data collection enterprise may be a food supplies distributor. The gateway or data center can be used to collect data from the data entry enterprise and to deliver that data to the data collection enterprise. In addition, the data center can be used to transmit software and/or data from the data collection enterprise and deliver the software and/or data to the data enterprise. Accordingly, data entry can be facilitated by the use of the hand-held computer to reduce the occurrence of human error in the data entry process. The hand-held computer typically operates in an off-line mode during data collection and will operate in an on-line mode for data transmission. The system also can include a cradle associated with each hand-held computer. The cradle can provide various data transmission functionality and can be used to initiate and support the on-line mode of operation. Alternatively, the cradle may be implemented as a pass-through device, providing only a functional connection to a network (e.g., telephone connector) and/or a power supply.

The system can include three main components. The first component is a computer or automated data collection system associated with the data collection enterprise. The second component is the gateway or data center, which provides a central location for data transmission and forms the majority of the computing required. The data center also processes and/or translates data transmitted between the data collection enterprise and the wireless hand-held terminals. The third component is the combination of the independent hand-held computer and the cradle. This combination is used by the data entry enterprise to enter, store, and transmit data to the data collection enterprise.

The advantages of the system and the method of the present invention are numerous. By enabling automated order entry, the system drastically reduces human error in data entry, thereby reducing operating costs and increasing profitability for all involved enterprises. The system can be implemented in connection with existing automated data entry systems, including internet-based

4

5      systems. The system of the present invention reduces the so-called accountability gap by associating all data entry with the corresponding data entry personnel. By controlling the data transmission and collection, the system of the present invention provides access to the collected data for analyses. In addition, the system can be configured so that the data collection enterprise can solicit data entry and transmission

10     by the data entry enterprise. This capability can reduce the likelihood of missed or forgotten data entry events.

The shape of the hand-held computer is another advantage of the present invention. The hand-held has a hand grip on one side and an input/output area on its top surface. The input/output area includes a combined display and a touchpad

15     input device. The display can be configured to render the visual output of the computer in four directions. The grip is designed to be ergonomically accommodating to a user's hand. The four-direction capabilities of the display and the shape of the hand grip are designed to accommodate both right and left handed users. The terminal can be manufactured without buttons, thereby using only virtual

20     buttons that are rendered by the display and activated by finger touch. This feature both simplifies the operation of the hand-held computer and eliminates the need for a stylus or any other additional input device.

The hand-held computer operates in combination with a cradle. The cradle is a separate piece of equipment that functions as the resting place for the hand-

25     held computer when not in use. The cradle also can function to provide a communication link between the hand-held computer and the data center. The cradle can include a detector that detects the presence of the hand-held terminal in the cradle. This detector can be used to switch the computer and/or cradle between active and standby modes of operation.

30     The various aspects of the present invention may be more clearly understood and appreciated from a review of the following detailed description of the disclosed embodiments and by reference to the drawings and claims.

**BRIEF DESCRIPTION OF THE DRAWINGS**

Figure 1 is a block diagram depicting an automated data entry system

35     that is an exemplary embodiment of the present invention.

5

Figure 2 is a block diagram depicting the primary components of an exemplary hand-held computer.

Figure 3 is a block diagram depicting the primary components of a cradle that is an exemplary embodiment of the present invention.

Figure 4 is a simplified drawing depicting the physical relationship of a hand-held computer that is disconnected from a cradle of an exemplary embodiment of the present invention.

Figure 5 is a simplified drawing depicting the physical relationship of the hand-held computer inserted into a cradle of an exemplary embodiment of the present invention.

Figure 6 is a perspective view of a hand-held data entry computer that is an exemplary embodiment of the present invention.

Figure 7 is a flow chart depicting an exemplary method for data entry and transmission between a hand-held data entry computer and a central computer.

Figure 8 is a simplified drawing depicting the top surface of an exemplary hand-held computer.

Figure 9 depicts an access display that may be used to restrict access to the operation of a data entry application running on a hand-held computer of an exemplary embodiment of the present invention.

Figure 10 depicts a hand-held computer displaying a top-level order-entry menu computer screen.

Figure 11 depicts an exemplary transmission display that may be rendered on the input/output area of a hand-held computer of an exemplary embodiment of the present invention.

Figure 12 is a flowchart depicting an exemplary method for managing and order entry transaction.

Figure 13 is a flowchart depicting an exemplary method for receiving and transmitting a credit request.

Figure 14 is a flowchart depicting an exemplary method for receiving and transmitting a request for distributor contact.

Figure 15 is a flowchart depicting an exemplary method for displaying previous orders.

Figure 16 is a flowchart depicting an exemplary method for transmitting information to a data center.

## DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENTS

An exemplary embodiment of the present invention provides a system and method for automated data entry using an independent hand-held computer. The present invention can be implemented as a gateway between a data entry enterprise and a data collection enterprise. The gateway or data center can be used to collect data from the data entry enterprise and to deliver that data to the data collection enterprise. Accordingly, data entry can be facilitated by the use of the independent hand-held computer to reduce the occurrence of human error in the data entry process. The hand-held computer will typically operate in an independent, off-line mode during data collection and will operate in an on-line mode for data transmission. The system also can include a cradle associated with each hand-held computer. The cradle can provide various data transmission functionality and can be used to initiate and support the on-line mode of operation.

The system can include three main components. The first component is a computer or automated data collection system associated with the data collection enterprise. The second component is the gateway or data center, which provides a central location for data transmission and forms the majority of the computing required. The data center also processes and/or translates data transmitted between the data collection enterprise and the independent hand-held computers. The third component is the combination of the hand-held computer and the cradle. This combination is used by the data entry enterprise to enter, store, and transmit data to the data collection enterprise.

The advantages of the system and the method of the present invention are numerous. By enabling automated order entry, the system drastically reduces

7

5    human error in data entry, thereby reducing operating costs and increasing profitability for all involved enterprises. The system can be implemented in connection with existing automated data entry systems, including internet-based systems. The system of the present invention reduces the so-called accountability gap by associating all data entry with the corresponding data entry personnel. By

10   controlling the data transmission and collection, the system of the present invention provides access to the collected data for analyses. In addition, the system can be configured so that the data collection enterprise can solicit data entry and transmission by the data entry enterprise. This capability can reduce the likelihood of missed or forgotten data entry events.

15              The shape of the hand-held computer is another advantage of the present invention. The terminal has a hand grip on one side and an input/output area consisting of a display and a touchpad on its top surface. The display can be configured to render the visual output of the terminal in four directions. The grip is designed to be ergonomically accommodating to a user's hand. The four-direction

20   capabilities of the display and the shape of the hand grip are designed to accommodate both right and left handed users. The computer can be manufactured without buttons, thereby using only virtual buttons that are rendered by the display. This feature both simplifies the operation of the hand-held computer and eliminates the need for a stylus or any other additional input device. The hand-held computer

25   operates in combination with a cradle. The cradle is a separate piece of equipment that functions as the resting place for the hand-held computer when not in use. The cradle also functions to provide a communication link between the independent hand-held computer and the data center. The cradle can include a detector that detects the presence of the hand-held computer in the cradle. This detector can be used to switch

30   the computer and/or cradle between standby and active modes of operation.

              Figure 1 is a block diagram depicting an automated order entry system that is an exemplary embodiment of the present invention. In a conventional restaurant supply distribution system, a distributor maintains a large inventory of restaurant supplies that can be ordered by a particular restaurant or a group of

35   restaurants. This is not unlike various other well-known distribution systems used to distribute goods and/or services. A common goal of these and other data

8

5    entry/collection systems is the elimination or reduction of data entry errors. Such errors can generate unnecessary expenses, loss of goodwill among customers, and other adverse effects.

In the automated distribution system of Figure 1, however, orders can be transmitted to a distributor's computer accurately and efficiently using an
10    automated system that is an exemplary embodiment of the present invention. Using the example of a restaurant supply distribution system, a distributor may maintain a central computer that accepts and processes orders and schedules delivery of those orders. In the automated order entry system, **100** of Figure 1, the distributor's computer is represented as the "Distributor's Data Processing (DP) System" **101**. A
15    second distributor may have a second Distributor's DP System **103**. Those skilled in the art will appreciate that any number of Data Processing Systems could be used to implement various embodiments of the present invention. Alternatively, a single Data Processing System could be used as a clearinghouse for multiple distributors.

The Distributors' DP Systems **101, 103** are connected to a data center
20    **106** (or gateway) via an Internet connection **108**. Those skilled in the art will appreciate that the connection between the Distributors' DP Systems **101, 103** and the data center **106** could be effected through various means of well-known data transmission, such as a conventional telephone connection. Alternatively, the Distributors' DP Systems **101, 103** could be implemented with the data center **106** as
25    a single, integrated computer system.

The data center **106** can be implemented as a central processing station for data and data transmissions. For example, the data center **106** can be used to aggregate data from various sources (e.g., various restaurants, various restaurant chains) and to sort and consolidate the aggregated data for transmission to a
30    distributor. The data center **106** can intelligently format and translate collected data so that it can be processed by distributors having varying data requirements. The data center **106** may be used to store data transmission profiles associated with each of the distributors to facilitate the data processing and to tailor the transmitted data to the distributors' needs. The data center **106** can also perform data processing to validate
35    certain verifiable data values, such as dates, quantities, etc. and can operate as a data

5　repository to store the histories of the data transmissions between the hand-held computers and the distributors.

　　　Orders can be submitted to the data center **106** via hand-held computers **102**. An order can be entered into a hand-held computer and then transmitted to the data center over a data transmission network **110** (e.g., a

10　conventional telephone system). The hand-held computer **102** can transmit the order to the data center **106** when the hand-held **102** is connected to the cradle **104**. Among other things, the cradle may be operative to provide a communication link between the hand-held computer **102** and the data center **106**, in cooperation with the data transmission network **110**. The data transmission network can be a telephonic

15　connection between the cradle **104** and the data center **106**. Alternatively, the data transmission network **110** can be an Internet connection between the cradle **104** and the data center **106**, or any other well-known means for data communication.

　　　An operator of the Distributor's DP System **101**, **103**, can transmit data to the hand-held computer **102** over the transmission network **110**. In the order-entry

20　context, for example, a distributor operating the Distributor's DP System **101** may submit an electronic order entry form for storage on a hand-held computer **102**. For example, a distributor's standard form may have changed and the new form can be transmitted to and stored on the hand-held computer **102**. In addition, all forms of data can be transmitted to the hand-held computer **102**. For example, the contents of

25　a previous order, a standard order, or an available product list (i.e., inventory list) may be transmitted to the hand-held computer **102** to assist in an order entry procedure. Accordingly, the automated order entry system **100** provides a two-way data communication system connecting a hand-held computer **102** with a Distributor's DP System **101**. Those skilled in the art will appreciate that various data communication

30　methodologies could be used to provide a communication link between the Distributor's DP System **101** and the hand-held computer **102**. In an exemplary embodiment of the present invention, real-time communication between the hand-held computer **102** and the Distributor's DP System **101** is not attempted when the hand-held computer **102** is disconnected from the data communication network **110** (e.g.,

35　not connected to the cradle **104**).

5          Figure 2 is a block diagram depicting the primary components of an
exemplary hand-held computer **102**. Generally stated, the hand-held computer **102** is
a general-purpose computing device implemented as a compact, hand-held user
interface. The hand-held computer **102** includes a processing unit **122**, a system
memory **124**, and a system bus **126** that connects various system components,
10   including the system memory **124** to the processing unit **122**. The hand-held
computer may also include a read-only memory (ROM) **128** and a random access
memory (RAM) **124**. The ROM **128** may store an operating system **130** that can be
transferred via the system bus **126** to the RAM **124**. The RAM **124** may also be used
to store applications **132** that can be executed by the processing unit **122**. The ROM
15   **128** may include a basic input/output system (BIOS) **134**. The BIOS **134** can contain
the basic computer instructions that enable the initial operation of the hand-held
computer at startup. For example, the BIOS **134** may initiate the transfer of the
operating system **130** from the ROM **128** to the RAM **124** at startup. Thereafter, the
RAM version of the operation system **131** will control the basic operation of the hand-
20   held computer **102**. Those skilled in the art will appreciate that the hand-held
computer **102** could use any of various other memory devices not shown in Figure 2,
such as a hard disk drive, a removable disk drive, a cassette drive, a flash memory
card reader, and the like.

        The hand-held computer **102** can connect to the cradle (**104**, Figure 1)
25   via a cradle connector **120**. The cradle connector **120** is connected to the
microprocessor and all other system components via the system bus **126**.
Communications over the cradle connector **120** with the cradle and with any other
network component connected to the communication network (**110**, Figure 1) can be
managed and controlled using a network interface **136**. Those skilled in the art will
30   appreciate that various well-known technologies could be implemented to provide the
functionality of the network interface **136**. In an alternative embodiment, the network
interface can be implement as part of the cradle, rather than as part of the hand-held
computer **102**. This alternative implementation may be used to simplify the design of
the handheld computer **102** or to reduce the weight of the handheld computer.

35          A user of the hand-held computer **102** may enter commands and data
into the hand-held computer using an input device, such as a touchpad **138**. The

11

5      touchpad is a well-known input device that operates in conjunction with a display panel **139** over which the touchpad is accurately registered. For example, the display panel **139** can display data, graphics, and virtual buttons. The user can touch the touchpad directly over these virtual buttons to input data. The touchpad **138** can be connected to the system bus **126** via touchpad interface **140**. The touchpad interface

10     **140** can operate to receive user input from the touchpad **138** for subsequent processing by the processing unit **122** and/or storage in memory, such as RAM **124**. The display interface **141** can also operate as a video rendering device receiving input from the processing unit **122** and causing the display panel **139** to render a graphic display. Because of the physical relationship of the touchpad **138** and the display

15     panel, which are spatially co-extensive, the term "touchpad" is often used herein to means the combination of the touchpad and the display panel.

The applications **132** can be stored and executed from the ROM **128**. Alternatively, the applications **132** can be stored and executed in the RAM **124**. As described in connection with Figure 1, the applications **132** may be transmitted to the

20     hand-held terminal **102** from the data center (**106**, Figure 1) or from the Distributor's DP System (**101**, Figure 1). Upon receipt of an application **132**, the hand-held computer **102** can recognize the application as such and store the application for subsequent execution. In a similar manner, data of various forms including inventory data, graphical data, program modules, operating system data, and the like can be

25     transmitted to the hand-held computer **102**. The operating system **130** and/or a specialized application **132** can be implemented to recognize and process the various forms of data that are received by the hand-held computer.

The hand-held computer **102** can be equipped with a battery pack that is not shown in Figure 2. The battery pack can supply power for the operation of the

30     components of the hand-held computer **102**, when the hand-held is connected to the cradle. The battery pack can be recharged when the hand-held computer **102** is returned to the cradle. The hand-held computer **102** can be supplied with power directly through the cradle connector **120** while the hand-held computer is connected to the cradle. The cradle connector **120** can also be used to supply power for a

35     recharging component (not shown) that can be built into the hand-held unit or the cradle to manage the recharging of the battery pack.

Figure 3 is a block diagram depicting the primary components of a cradle **104** that is an exemplary embodiment of the present invention. The primary components of the cradle **104** are interconnected by a system bus **152**. A processing unit **142** primarily controls the function of the other components and manages communications with the hand-held computer **102** (Figure 2) via the cradle connector **150**. The cradle connector **150** goes with the cradle connector **120** of the hand-held computer **102**. When the cradle connectors are functionally coupled, the cradle **104** and the hand-held computer **102** can communicate. In addition, the cradle **104** can provide power to the hand-held computer **102** through the cradle connector **150**. Those skilled in the art will appreciate that the cradle **104** can itself be connected to a power source, such as an AC power supply. It will also be appreciated that the cradle **104** may contain a power processing unit, such as a transformer to provide power to the cradle's components, as well as to the hand-held computer **102**.

The hand-held computer **102** can be inserted into the cradle in the direction of arrow **156**. The cradle **104** includes a device port **154** that has a shape that substantially conforms to a leading edge of the hand-held computer **102**, such that the cradle connectors of the hand-held computer and of the cradle can be functionally coupled.

The cradle **104** also may include a hand-held detector **144** which detects the presence of the hand-held computer in the port **154**. When the detector **144** detects the presence of the hand-held computer **102** in the port **154**, communication between the hand-held terminal and the cradle can be commenced.

The cradle **104** also can include a read-only memory (ROM) **148**. The ROM **148** can be used to store an operating system, a BIOS, application programs, and any other program module and/or data that is useful to the hand-held computer **102** and the cradle **104**.

The cradle **104** can be connected to the network **110** via network connector **158**. The network connector **158** can be implemented as any of a number of well-known connectors, such as the standard two wire telephone connector or a standard Ethernet connector. The cradle can also include a modem **146** for enabling communication between the cradle **104** and/or the hand-held computer **102** with the network **110** and other network elements (e.g., Distributor's DP System **101**, data

13

5   center **106**). The processing unit **142** can route the data received over the network connector **158** to, for example, the ROM module **148** or the hand-held computer **102**. In an alternative embodiment, the processing unit **122** of the hand-held computer **102** can perform this routing function.

Accordingly, the cradle **104** can function as the network intermediary 10  between the hand-held computer **102** and the network **100**. When the hand-held computer **102** is inserted into the port **154** of the cradle **104**, the hand-held detector **144** can indicate to the processing unit **142** that the hand-held computer is present. The processing unit **142** can perform a hand-shaking process to ensure proper communication between the cradle **104** and the hand-held computer **102**. Once 15  proper communication has been established, the processing unit **142** may determine whether the hand-held unit **102** has a pending transmission (e.g., an order to be transmitted to the distribution system **101**). If the processing unit **142** determines that the hand-held unit **102** has a pending transmission, the processing unit **142** will initiate a communication session with the appropriate network element, such as the 20  data center **106**.

This communication session can be established by use of the modem **146** in conjunction with the network connector **158**. For example, with a telephonic connection, the processing unit **142** may cause the modem **146** to establish a telephonic connection with the data center **106**. The processing unit **142** can perform 25  a second hand-shaking process to ensure proper communication between the hand-held computer **102** and the data center **106**. Once the telephonic connection has been established, the processing unit **142** can instruct the hand-held computer **102** to begin to transmit its pending transmission. Those skilled in the art will appreciate that the processing unit **122** of the hand-held computer could perform all of the functionality 30  ascribed to the processing unit **142** of the cradle **104**.

If the hand-held computer **102** does not have a pending transmission, upon insertion into the cradle **104**, the processing unit **142** of the cradle may enable the transmission of data to the hand-held computer. The automated order entry network **100** of an exemplary embodiment of the present invention contemplates two- 35  way communication. For example, the distribution system **101** and/or the data center **106** may transmit data and/or program modules to the hand-held computer.

14

5          In an alternative embodiment, the cradle may be implemented as a pass-through device, providing only a functional connection to the network (e.g., telephone connector) and/or to the power supply. In this alternative embodiment, the cradle may have a telephone connector that can be virtually always connected to a functioning telephone line. The connectors of the hand-held computer and the cradle

10       can provide the functional connection to connect the hand-held device with the telephone line. The connectors also could provide this sort of pass-through connection to a power supply connected to the cradle. In this alternative embodiment, the hand-held presence switch and the modem (and all other functional components) could be integrated in the hand-held device itself. Accordingly, all of the cradle

15       functions described above would be performed by the hand-held device, rather than by the cradle.

Figure 4 is a simplified drawing depicting the physical relationship of a hand-held computer **102** that is disconnected from a cradle **104** of an exemplary embodiment of the present invention. The hand-held computer **102** can be inserted

20       into the cradle **104** by moving the hand-held computer in the direction of arrow **200**. The leading edge **202** of the hand-held computer **102** is inserted into the port **204** of the cradle **104**. Figure 4 is a side, elevation view of the hand-held computer **102** and the cradle **104**. Dashed lines on the hand-held computer **102** depict the touchpad **206** and the grip **208**. The touchpad **206** and the grip **208** are shown and described in

25       more detail in connection with Figure 6.

Figure 5 is a simplified drawing depicting the physical relationship of the hand-held computer **102** inserted into a cradle **104** of an exemplary embodiment of the present invention. Figure 5 depicts the hand-held computer **102** after it has been inserted into the port **204** of the cradle **104**. As shown in Figure 5, the leading

30       edge of the hand-held computer **102** is no longer visible as it is located within the port **204**. Although a portion of the touchpad **206** has also been inserted into the port **204**, in one embodiment of the present invention, the cradle **104** can include a viewing window that enables the display panel to be seen, even when the hand-held computer **102** is inserted in the cradle **104**.

35          Figure 6 is a perspective view of a hand-held data entry computer **102** that is an exemplary embodiment of the present invention. The hand-held computer

5    250 includes a touchpad **252** that displays information and operates as an input device, enabling a user to touch portions of the touchpad to instruct the hand-held computer to perform various functions. The hand-held computer **250** is ergonomically designed to be held comfortably by data entry personnel. A grip channel **254** is designed to accommodate the thumb and the portion of a user's hand

10   adjacent to the thumb. The grip channel can extend along substantially the entire edge of the hand-held computer **250**. In an alternative embodiment, the grip channel **254** can have a longitudinal dimension less than the entire length of the hand-held computer **250**. In any case, the grip channel **254** can be equipped with a texture to create a tackier surface, such as a knurled surface.

15          The hand-held computer also includes a grip handle **256**. The grip handle can also extend along substantially the entire length of the hand-held computer **250**. In an alternative embodiment, the grip handle **256** can extend along less than the entire length of the hand-held computer **250**. The grip handle **256** is designed to accommodate the fingers of the user. Accordingly, the user can hold the hand-held

20   computer **250** by placing its thumb in the grip channel **254** and wrapping its fingers around the grip handle **256**. The grip can be used to extract the hand-held computer **250** from its cradle (not shown) and to stabilize the hand-held computer during order entry (i.e., while the user operates the touchpad **252**). Advantageously, in an exemplary embodiment of the present invention, the hand-held computer **250** can be

25   manufactured such that it is physically symmetric along an axis perpendicular to the grip channel **254**. In this embodiment, the hand-held computer **250** is ambidextrous, in that the user can hold the hand-held computer with either a right hand or a left hand. The display of the hand-held computer **250** that is rendered in combination with the touchpad **252** can be inverted to accommodate this feature of the hand-held

30   computer **250**. In an alternative embodiment, the display can be rendered in any one of four orientations, such that the display can be view form any one side of the hand-held computer.

          Figure 7 is a flow chart depicting an exemplary method for data entry and transmission between a hand-held data entry computer and a central computer.

35   The method of Figure 7 begins at start block **300** and proceeds to step **302**. At step **302**, the hand-held computer is removed from the cradle. In the context of a

5    restaurant, the restaurant personnel may move the hand-held from its cradle when an order needs to be sent to the inventory supply distributor. Typically, orders include regularly scheduled orders, such as a monthly or weekly orders or impromptu orders, such as when a particular inventory item has been unexpectedly exhausted.

The method proceeds from step 302 to step 304. At step 304, an order

10    is entered into the hand-held computer. An exemplary order entry method is described in more detail below in connection with Figures 8 - 16. The method proceeds from step 304 to step 306. At step 306, the hand-held computer is returned to the cradle. As described above in connection with Figures 1 - 3, the return of the hand-held computer to the cradle can trigger the initiation of a transmission between

15    the hand-held computer and the central computer. For example, a hand-held detector may recognize a functional connection between the hand-held computer and the cradle. When this connection is recognized, a determination may be made as to whether the hand-held computer includes a pending order (i.e., a yet to be transmitted order) or other pending data. A separate determination may be made as to whether

20    the central computer has indicated a need to transmit data to the hand-held computer. The central computer may indicate such a need by, for example, storing a transmission request in a memory location in the cradle. Alternatively, the hand-held computer may be configured to request any such transmissions from the central computer upon insertion into the cradle.

25    A method proceeds from step 306 to step 308. A step 308, a session is established between the central computer and the hand-held computer. As described above in connection with Figure 3, an exemplary cradle may be a pass through connector between a modem in the hand-held computer and a network interface, or may include a modem and/or a network connector that can initiate a functional data

30    communication link with the central computer. The modem may dial a predetermined telephone number to gain access to a modem pool associated with the data center.

In an alternative embodiment of the present invention, a session may be established with the data center by accessing an internet protocol (IP) address associated with the data center. For example, the combination of the hand-held

35    computer and the cradle may be configured to access a predetermined website associated with the central computer and may transmit information between the hand-

17

5    held computer and the central computer in, for example, HTML format, XML format, ASCII format, or Unicode format allowing the use of worldwide alphabets and languages on the display panel.

The method proceeds from step **308** to step **310**. At step **310**, the order is transmitted to the data center. The method proceeds to step **312**, wherein the hand-

10   held computer is reset (e.g., the order is denoted as having been transmitted). The method proceeds from step **312** to step **314**. At step **314**, the memory of the hand-held computer is updated. The memory update may include resetting the order entry forms and moving a transmitted order from a pending order location to a transmitted order memory location. The memory update may include the transmission of new or

15   replacement applications from the central computer to the hand-held computer's memory. The memory update may also include the removal of old order entry records and the replacement of operating system modules and/or any other program modules stored in the hand-held computer's memory. In an alternative embodiment of the present invention, step **314** may also include the updating of memory in the

20   cradle.

The method proceeds from step **314** to step **316**. At step **316**, the communication session with the data center is terminated. In this step, the hand-held computer may return to a stand-by mode and await either the removal from the cradle, a communication session initiated by the central computer, or an entry session

25   initiated by a user's touching the touchpad. The method proceeds from step **316** to end block **318** and terminates.

Figure 8 is a simplified drawing depicting the top surface of an exemplary hand-held computer **320**. The touchpad **322** of the hand-held computer **320** is displaying a default screen that can be displayed when the hand-held computer

30   is in a stand-by mode. As described above in connection with Figure 7, the hand-held computer may maintain a stand-by mode when it is inserted in the cradle. In this mode, hand-held computer's touchpad may display the name of the organization to which it is associated **324** (e.g., "Downtowner Grill"). The touchpad may also display the date and time **326**. The default display of the touchpad may also include the

35   instruction to remove the hand-held computer from the cradle for use. In an alternative embodiment, the hand-held computer may be equipped to operate while

18

5    connected to the cradle.  In such an alternative embodiment, the removal instruction
**328** may be eliminated from the stand-by mode display (i.e., the default display).

Figure 9 depicts an access display **330** that may be used to restrict
access to the operation of a hand-held data entry computer **320** of an exemplary
embodiment of the present invention.  In this exemplary access display **330**, and
10   instruction message **332** instructs the user to enter an access code or a user ID.  The
input/output area **322** can display a virtual keypad **324**, which can be used by the user
to enter a sequence of numbers corresponding to the user's access code.  Following
entry of the access code, the user can press a virtual "enter" button **336** to submit the
access code to the hand-held computer.  The user may cancel an erroneous access
15   code entry by pressing the virtual "clear" button **338**.  Once a correct access code or
user ID has been entered into the hand-held computer **320**, access to the other
functionality of the hand-held can be granted to the user.

Figure 10 depicts a hand-held computer **320** with a display that is
displaying a top-level order-entry menu computer screen **340**.  The menu screen **340**
20   includes an on-screen instruction **342**, instructing the user to select a task by pressing
a virtual button displayed in the menu screen **340**.  In the order entry context, the
buttons may include a "place order" button **344**, a "credit request" button **346**, a
"contact distributor" button **348**, a "review previous order" button **350**, and a
"reset/send" button **352**.  Those skilled in the art will appreciate that the virtual
25   buttons depicted in Figure 10 pertain to the use of an exemplary hand-held computer
**320** in the order-entry context.  It will be further appreciated that the various other
virtual buttons may be appropriate to the use of the exemplary hand-held computer
**320** in other data entry context.  Although the use of the automated data entry system
is described in the general context of order entry and in the specific context of a
30   restaurant distribution system, it will be appreciated that the automated data entry
system could be used in a variety of data entry context.

The "place order" virtual button **344** can be used to initiate the order
entry functionality of the hand-held computer **320**. The "credit request" virtual button
**346** may be used to transmit a credit request form to a central computer for
35   subsequent processing.  The "contact distributor" virtual button **348** may be used to
transmit a request for a subsequent communication with the personnel of the

19

5     distributor. The "view previous order" virtual button **350** may be used to display a history of previously transmitted orders. Finally the "reset/send" virtual button **352** may be used to cancel a pending order (i.e., and entered but not transmitted order) or to transmit a pending order. The operation of the hand-held computer **320** following the election of one of the virtual buttons **344-352** will be described in more detail in

10    connection with Figures 12 through 16.

Figure 11 depicts an exemplary transmission display that may be rendered on the input/output area **322** of a hand-held data entry computer **320** of an exemplary embodiment of the present invention. The transmission display **354** can include a warning **356** notifying the user that the transmission operation is in progress.

15    The transmission operation can be performed when the hand-held computer **320** has been returned to its cradle or when a transmission has been initiated by the central computer. Typically, the removal of the hand-held computer **320** from the cradle during transmission will prohibit a complete transmission. Accordingly, a non-removal instruction **358** can be displayed to warn the user to avoid removal from the

20    cradle. Finally, the transmission display **354** can display progress information, such as time remaining data **360** or a progress bar **362**.

Figure 12 is a flowchart depicting an exemplary method for managing and order entry transaction. The method begins at start block **400** and proceeds to step **401**. At step **401**, the "place order" selection is made. Typically, this selection

25    will be made by a user pressing the "place order" virtual button on the touchpad of the hand-held device. The method proceeds from step **401** to step **402**. At step **402**, the user is prompted to enter a delivery day and the delivery day is set. The user may be asked to enter a delivery day or a default delivery day may be provided that can be verified or modified.

30    The method of Figure 12 proceeds from step **402** to step **406**. At step **406**, the standard order is displayed. Typically, there will be a standard order associated with either the user or the hand-held device. This standard order can be displayed to facilitate the order entry process. In an alternative embodiment, the user may be provided with a completely blank order entry form that does not include any

35    standard order information. The method proceeds from step **406** to decision block **404**, wherein a determination is made as to whether the user desires to return to the

20

5    main menu. The user may at any time select to return to the main menu, thereby terminating the order entry process. If a determination is made that the user desires to return to the main menu without completing the order entry process, the method may branch from decision block **404** to step **420**. At step **420**, the main menu is displayed. The method proceeds from step **420** to end block **421** and terminates. In an

10   alternative embodiment, the order entry procedure can be placed on "hold," when the user returns to the main menu, such that any entered order information can be retained and the order entry process can be resumed.

Returning to decision block **404**, if a determination is made that the user has selected to return to the main menu, the method proceeds from decision

15   block **404** to manual actions **408-419**. These actions can be performed by the user at the same point in the method of Figure 12. The user may perform any of the actions **408-419** at this point in the exemplary method. While the standard order is still displayed, as performed in step **406**, the user may selected a "page up" option **408** or a "page down" option **410**. These options enable the user to navigate through the pages

20   of a displayed standard order or any other order that is displayed. The user may control the quantity of an order item by selecting a "quantity down" option **412** or a "quantity up" option **414**. For example, if an item on the standard order is associated with a standard quantity (i.e., a par value) that is too high or too low for the user's immediate needs, the quantity options **412, 414** may be used to modify the quantity.

25   User may also select an option to add an item from the full inventory **416**. This option is used to modify the standard order or to modify any order that is being edited by adding an item from a full inventory list. The full inventory list may be transmitted from the data center to the hand-held computer and stored in memory. Alternatively, the full inventory list may be maintained on the data center and

30   accessed in real time by the hand-held computer on a page-by-page basis. In any event, once the item has been added to a particular order, the quantity of that item can be adjusted as described above.

The user may also be provided with a "select item value" option **418**. If the user selects the "select item value" option **418**, the user may be provided with

35   two other sub-options, the "set locale value" option **424** and the "set par value" option

21

5  **426.** If the user selects the "set locale value" option **424**, the method proceeds to step **432** and a number representing the location in the standard order for a particular item may be entered. This locale value is useful for organizing a standard order, such that associated items can be sequenced together. For example, all frozen items may be grouped together within the standard order by assigning similar and/or consecutive

10  local values to those items.

This sequencing can exploit the off-line order entry capabilities of the hand-held computer. One of the benefits for having the off-line order entry capabilities of the exemplary hand-held computer is to enable the entry of an order "or other data" in a manner that allows the order entry personnel full freedom of motion.

15  The locale value method of order entry further expedites the order entry process by enabling the creation of a sequence standard order. Accordingly, in the context of an exemplary restaurant order entry process, the order entry personnel may follow an established path through a stockroom, a refrigerator, a freezer, and the like. Of course, this is true for any data entry user of the hand-held computer. For example, if

20  the hand-held computer is used for data entry and any context that utilizes a predetermined sequence, the locale value standard order structure can be beneficial.

Returning to Figure 12, another item value that can be set is the par value. The user selects the "set par value" option **426**, the method will proceed to step **430** and a default par value associated with an item in the standard order may be

25  modified.

Selection of any of the menu options **408-416, 424, 426** can result in the display of the updated current order at step **429**. Thus, at step **429**, the new order or a revised currently edited order will be displayed. The method proceeds from step **429** to decision block **404**. At decision block **404**, a determination is made as to

30  whether the user desires to return to the main menu and proceeds as described as above. At any point in the process, the user may perform the manual operation of replacing the hand-held in the cradle **419**. If the user places the hand-held in the cradle, the method will proceed from manual operation **419** to step **428**. At step **428**, any pending order and/or other information will be transmitted to the data center. The

5        method proceeds from step **428** to end block **421** and terminates.  Once the order has been transmitted, the hand-held will return to a standby mode as described above.

Figure 13 is a flowchart depicting an exemplary method for receiving and transmitting a credit request.  Method of Figure 13 begins at start block **448** and proceeds to **450**.  At step **450**, a "credit request" option is selected.  The method

10       proceeds from step **450** to decision block **452**, wherein a determination is made as to whether the credit request is confirmed.  Typically, the operation of decision block **452** is performed by the hand-held computer prompting the user to confirm the user's request to notify a distributor of the credit request.  If a determination is made that the user has not confirmed the credit request, then it will branch to decision block **454**.

15       At decision block **454**, a determination is made as to whether the user has selected to return to the main menu.  If such a selection has been made, the method proceeds to step **459** and the main menu is displayed.  The method proceeds from step **459** to end block **461** and terminates.

Returning now to decision block **454**, if a determination is made that

20       the user has not selected to return to the main menu, the method branches from decision block **454** to step **455**.  At step **455**, the user is instructed to place the hand-held in the cradle.  The method proceeds from step **455**, to decision block **456**, wherein a determination is made as to whether the hand-held has been replaced in the cradle.  If the hand-held has not been replaced it the cradle, the method branches from

25       decision block **456** to step **455**, and the user is prompted to return the hand-held to the cradle until the user does so.  If a determination is made at decision block **456** that the hand-held has been replaced in the cradle, the method proceeds from decision block **456** to step **458**.  At step **458**, the credit request is transmitted to the data center.  The method proceeds from step **458** to end block **461** and terminates.

30       Returning now to decision block **452**, if a determination is made that the credit request is confirmed, the method branches from decision block **452** to step **453**.  At step **453**, the user is prompted for any needed credit request information.  The method proceeds from step **453** to decision block **456** and proceeds as described above.

23

5    Figure 14 is a flowchart depicting an exemplary method for receiving and transmitting a request for distributor contact. The method begins at start block **460** and proceeds to step **461**. At step **461**, the user selects the "contact distributor" option. When the user selects the "contact distributor" option, the user will be provided with a sub-menu of options represented by annual operations **462-474**. The

10    available options **462-474** are generally means for routing a contact request to a particular department associated with the distributor. Accordingly, the options may include a "customer service representative" option **462**, a "sales representative" option **466**, a "quality control representative" option **468**, a "transportation department" option **470**, a "vice-president of sales" option **472**, and a "vice-president

15    of service" option **474**. Those skilled in the art will appreciate that these option titles are arbitrary in any routing destination identifier could be used to distinguish one option from the others. The method proceeds from manual operations **462-474** to step **475**. At **475**, the user is prompted to supply any needed contact information. The method proceeds from step **475** to decision block **481**..

20    At decision block **481**, a determination is made as to whether the user has selected to return to the main menu. If such a selection has been made, the method proceeds to step **483** and the main menu is displayed. The method proceeds from step **483** to end block **485** and terminates.

      Returning now to decision block **481**, if a determination is made that

25    the user has not selected to return to the main menu, the method branches from decision block **481** to step **479**. At step **479**, the user is instructed to place the hand-held in the cradle. The method proceeds from step **479**, to decision block **477**, wherein a determination is made as to whether the hand-held has been replaced in the cradle. If the hand-held has not been replaced it the cradle, the method branches from

30    decision block **477** to step **479**, and the user is prompted to return the hand-held to the cradle until the user does so. If a determination is made at decision block **477** that the hand-held has been replaced in the cradle, the method proceeds from decision block **477** to step **487**. At step **487**, the contact request is transmitted to the data center. The method proceeds from step **487** to end block **485** and terminates.

24

5    Figure 15 is a flowchart depicting an exemplary method for displaying previous orders. The method of Figure 15 begins at start block **490** and proceeds to step **492**. At step **492**, the "view previous orders" option is selected. Typically, the user will select the "view previous orders" option to review orders that have been entered in the hand-held computer and stored in memory. The method proceeds from

10   step **492** to step **494** and a previous order list is displayed. The previous order list can include orders that were recently transmitted to the data center. A policy may be established as to the number of list items maintained in the hand-held computer's memory. For example, the hand-held computer could be configured to delete orders that are more than thirty days old or to delete orders causing the previous order list to

15   exceed a predefined number of orders. The method proceeds from step **494** to decision block **496**. At decision block **496**, a determination is made as to whether the user has selected a particular order. If the user has selected a particular order, the method branches to step **500**. At step **500**, the selected order is displayed. When the user is finished viewing the displayed selected order, the method proceeds from step

20   **500** to end block **502** and terminates.

Returning now to decision block **496**, if a determination is made that an order is not selected, the method branches from decision block **496** to step **498**. At step **498**, a determination is made as to whether the user has selected to return to the main menu. If the user has selected to return to the main menu, the method branches

25   to step **504**, wherein the main menu is displayed. The method proceeds from step **504** to end block **502** and terminates. If at decision block **498**, a determination is made that the user has not chosen to return to the main menu (and has not selected an order for display), the method branches to step **494** and the previous order lists remain displayed until either an order is selected or the user selects to return to the main

30   menu.

Figure 16 is a flowchart depicting an exemplary method for transmitting information to a data center. The method of Figure 16 begins at start block **506** and proceeds to step **508**. As step **508**, the "reset/sent" option is selected. The method proceeds form step **508** to step **512**, wherein the user is instructed to

35   replace the hand-held computer in the cradle. The method proceeds from step **512** to

5    decision block **510**, wherein a determination is made as to whether the user has replaced the hand-held in the cradle. If a determination is made at decision block **510** that the user has not placed the hand-held in the cradle, the method branches to step **514** and a determination is made as to whether user has selected to return to the main menu. If the user has not selected to return to the main menu, the method branches to

10   step **512** and the user is continually instructed to replace the hand-held in the cradle until the user does so or selects to return to the main menu. If, on the other hand, a determination is made at decision block **514** that the user has selected to return to the main menu, the method branches to step **520** and the main menu is displayed. The method proceeds from step **520** to end block **518** and terminates.

15                          Returning now to decision block **510**, if a determination is made that the hand-held has been replaced in the cradle, it branches to step **516**. At step **516**, any pending information in the hand-held computer will be transmitted to the data center as described above. The method proceeds from step **516** to end block **518** and terminates.

20           Although the present invention has been described in connection with various exemplary embodiments, those of ordinary skill in the art will understand that many modifications can be made thereto within the scope of the claims that follow. Accordingly, it is not intended that the scope of the invention in any way be limited by the above description, but instead be determined entirely by reference to the claims

25   that follow.